



# Commercial Air & Surface Purification System

OMNI by GreenTech is the next generation in air and surface purification designed to reduce germs, odors, and chemical contamination throughout the indoor environment. In food safety applications OMNI is the most cost-effective means for significantly reducing environmental microorganisms and pathogens such as *Bacillus globigii*, *Staphylococcus aureus*, *Candida albicans*, *Stachybotrys chartarum*, *Pseudomonas aeruginosa*, *Escherichia coli*, *Streptococcus pneumoniae*, and *Listeria monocytogenes*.

The disinfection technology within OMNI can be used in food processing, food preparation, food and ice storage, and food transportation for the control and prevention of disease-causing microorganisms while remaining safe for human exposure. By reducing pathogens on food contact surfaces, OMNI decreases cross-contamination and improves the quality of shelf-life of food products.

The odor reducing capability also makes OMNI a perfect choice for commercial restrooms or any location in which odor reduction is needed. Unlike cover-up chemicals, OMNI breaks down the biological components thereby eliminating the odor. The result is a fresh smelling and sanitary environment.



## Benefits of OMNI

Reduces VOC Levels

Prolongs Food Shelf-Life

Prevents Disease-Causing Microorganisms

Eliminates Pathogens

Significantly Reduces Odors

Improves Food Safety

## Features & Specifications

### Features

- Convenient Wall Mounting
- Glowing Unit Operating Window
- Optional Ported Blower Plate & Hoses
- Sleek & Easy to Maintain
- Replaceable PCO Cell

### Unit

- Dimensions: 18.5" H (470mm) x 6.30" W (160mm) x 4.40" D (112mm)
- Weight: 4.7lb/ 2.13kg
- Material: Powder Coated Aluminum or Stainless Steel
- Optional Hose Kit: Directs the purification to contained spaces such as food storage, display cases, small ducting, or more.
- Warranty: 2 Year Manufacturer's Warranty

### Technologies

- Photo-Catalytic Oxidation
- Germicidal UV Disinfection (Ozone or Non-Ozone Producing)

### Performance

- Ozone Output: <0.05 ppm
- Coverage: 8000 ft.3 or 1000 ft.2
- Airflow: 10 CFM (grill application), 3CFM (ported application)

### Power

- Input Voltage: 100-240 VAC 50/60Hz
- Operating Voltage: 12VDC
- Operating Wattage: 10.9W
- Operating Amperage: .91A

### Packaging

- Dimensions: 7.25" H (184mm) x 9.50" W (241mm) x 27.5" D (699mm)
- Weight: 4.2lb (1.9kg)

